

**Generating Set Functional Test Report**  
In accordance with ISO 8528 - 6 2005

PLANT NUMBER: E9769 CE: No

RATED OUTPUT	KVA	<u>65</u>	RATING CLASSIFICATION	<u>PRP</u>			
	KW	<u>52</u>					
	PHASE	<u>3</u>					
	VOLTS	<u>380/220</u>			PERFORMANCE CLASS	<u>G1</u>	
	AMPS	<u>99</u>					(AS DEFINED BY ISO 8528-1)
	HZ	<u>50</u>					
	RPM	<u>1500</u>					
GOVERNOR TYPE	<u>Mechanical</u>	COOLING METHOD	<u>WATERCOOLED</u>				

ENGINE MAKE	<u>Perkins</u>	BUILD NUMBER	<u>RS51276</u>
ENGINE MODEL	<u>1104A-44TG1</u>	SERIAL NUMBER	<u>US131394</u>
ALTERNATOR MAKE	<u>Mecc Alte</u>		
ALTERNATOR MODEL	<u>ECP 34-1S/4</u>	SERIAL NUMBER	<u>A1092659</u>
CONTROL PANEL(S)	<u>Manual start</u>	SERIAL NUMBER(S)	
SWITCHGEAR		SERIAL NUMBER(S)	

**LOAD TEST RESULTS (AT UNITY POWER FACTOR)**

LOAD TYPE	LOAD %	HZ	VOLTS	AMPS	KW	ENGINE TEMP DEG C	OIL TEMP DEG C	OIL PRESS BAR
load acceptance	<u>100%</u>	<u>50.2</u>	<u>380</u>	<u>79</u>	<u>52</u>	<u>-</u>	<u>-</u>	<u>5.3</u>
standby/prime+10%	<u>110%</u>	<u>50.0</u>	<u>380</u>	<u>87</u>	<u>57</u>	<u>84</u>	<u>-</u>	<u>3.9</u>

GENERATING SET ENCLOSURE MECHANICAL PROTECTION: IP

AVERAGE SOUND PRESSURE LEVEL (DBA AT 1 M)

(UNITS WITH ACOUSTIC CANOPIES ONLY & MEASURED UNDER TEST BAY CONDITIONS AT 75% LOAD IN ACCORDANCE WITH ISO8528-10)

AMBIENT TEST CONDITIONS		FUEL/OIL USED	
ALTITUDE (M)	<u>Sea Level</u>	FUEL SPEC	<u>BS2869A2</u>
BAROMETRIC PRESSURE (kpa)	<u>101.9</u>	DENSITY	<u>0.84 kg/l</u>
TEMPERATURE (Deg c)	<u>14</u>	CALORIFIC VALUE	<u>42.5 MJ/kg</u>
HUMIDITY (%)	<u>88</u>	LUB OIL SPEC	<u>Multigrade</u>

**WIRING DIAGRAMS:**

ENGINE	<u>06-130700</u>	CONTROL PANEL(S)	<u>10-170800</u>
--------	------------------	------------------	------------------

TESTED BY: H. Wal

DATE: 07/10/2010